




A206

• Display screen: 7.0 inches • Support live detection • Wide Dynamic Camera • Support 5000/10000 face database • Recognition speed: 250ms • Recognition rate: $\geq 97\%$ • Support Wigan signal output • Communication mode TCP/IP	• Display screen: 5.0 inches • Support live detection • Support 5000/10000 face database • Recognition speed: 250ms • Recognition rate: $\geq 97\%$ • Support Wigan signal output • Communication mode TCP/IP
Face recognition device (panel)/DF101	Face recognition device (column)/DF102

Product Size



Parameters

Material	SUS304 1.5/1.2mm
Size	1400*300*1020 mm
Sensor pairs	5
Pass rate	35p/m
Pass width	550mm
Input voltage	100V~240V
Motor type	24V DC brush motor
Environment	-20~+70°C
Motor power	35W
Input signal	Dry contact/RS485

Functions & Features

- Reasonable and reliable design, low noise, smooth operation and long service life;
- With function of opening doors automatically under power-off state to meet the need of fire-fighting passage;
- With functions of anti-tail, anti-reverse pass and so on;
- Card can be set "with memory" or "without memory" functions;
- With automatic reset function, i.e. after having access to the gate, the gate automatically restores to the locked state if not pass within the time set;
- With infrared anti-clip function (anti-clip when gate is open or running);
- Compatible with IC, ID card, scanning and face recognition, etc.
- Two modes of operation are available: open or closed.
- Various working modes are available, including two-way card reading and one-way card reading, etc.